

Product Name: **MX Nylon**

Preparation date: 2/8/05

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MSDS REVISION #: 009

PRODUCT NAME: MX Nylon
(Grades 6001, 6007 and 6121)

SYNONYMS: Polyamide MXD6, Nylon MXD6

DISTRIBUTED BY: Mitsubishi Gas Chemical America, Inc.
655 Third Avenue, 24th Floor
New York, NY 10017

PHONE NUMBERS: Inquiries - (212) 687-9030 (business hours)
CHEMTREC - (800) 424-9300 (transportation emergencies)

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

<u>Component</u>	<u>%</u>	<u>CAS No.</u>	<u>Exposure Limits</u>
Hexanedioic acid, polymer with 1,3-benzenedimethanamine	100	25718-70-1	Not established

SECTION 3 - HAZARDS IDENTIFICATION

***** **EMERGENCY OVERVIEW** *****

Although there are no known or expected hazards associated with handling this product, this and all industrial chemicals should be handled with caution.

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.

POTENTIAL HEALTH EFFECTS

EYES:
No adverse health effects known or expected.

SKIN:
No adverse health effects known or expected.

Product Name: **MX Nylon**

Preparation date: 2/8/05

SECTION 3 - HAZARDS IDENTIFICATION (continued)

INGESTION (swallowing):

No adverse health effects known or expected.

INHALATION (breathing):

Fumes from processing cause irritation to certain sensitive individuals and aggravate pre-existing lung disorders.

CHRONIC EFFECTS/CARCINOGENICITY:

This product (or component) is not listed in IARC Monographs, the NTP Ninth Annual Report or the ACGIH TLVs as a carcinogen or potential carcinogen. OSHA does not regulate it as a carcinogen.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT:

Flush with large amounts of water, lifting upper and lower lids occasionally. Get medical attention.

SKIN CONTACT:

Wash exposed area with soap and water.

INHALATION (breathing):

If affected, move to fresh air. If breathing is difficult, call a physician.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: 628° F (331° C)

FLASH POINT METHOD: Unavailable

UPPER EXPLOSION LIMIT:

Unavailable

LOWER EXPLOSION LIMIT:

Unavailable

AUTOIGNITION TEMPERATURE:

725° F (385° C)

EXTINGUISHING MEDIA:

Water spray, carbon dioxide, dry chemical or foam

Section 5 continued on next page

Product Name: **MX Nylon**

Preparation date: 2/8/05

SECTION 5 - FIRE FIGHTING MEASURES (continued)

FIRE AND EXPLOSION HAZARDS:

Finely divided polyamide dusts, when dispersed in air may pose a dust explosion hazard. All material handling equipment that may generate dust clouds of the product should have properly designed explosion relief/suppression systems.

FIRE-FIGHTING EQUIPMENT:

Wear full protective clothing and self-contained breathing apparatus with full face-piece. Combustion products may include toxic fumes.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Persons not wearing protective equipment should be excluded from the area of the spill until clean up has been completed. Shovel spilled material into containers. Thoroughly sweep up residual material.

SECTION 7 - HANDLING AND STORAGE

Keep in closed or covered containers when not in use. Store in cool dry place with adequate ventilation. Wash thoroughly after handling.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

Not required under normal conditions of use.

SKIN PROTECTION:

Wear protective gloves.

EYE PROTECTION:

Protective eye wear or safety glasses are recommended.

ENGINEERING CONTROLS:

Fumes from thermal processing equipment should be ventilated from the work area.

Product Name: **MX Nylon**

Preparation date: 2/8/05

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Pellets @ 77° F (25° C)
ODOR THRESHOLD:	Unavailable
SPECIFIC GRAVITY:	1.2 - 1.23
VAPOR PRESSURE (mm Hg):	Nil
VAPOR DENSITY (Air = 1):	Not applicable
INITIAL BOILING POINT:	Decomposes
EVAPORATION RATE: (Ethyl Ether = 1)	Nil
SOLUBILITY in WATER:	Insoluble
BULK DENSITY:	0.6 - 0.8
VOLATILE %:	Nil
pH:	Unavailable
pH METHOD:	Not Applicable

SECTION 10 - STABILITY AND REACTIVITY

STABILITY (conditions to avoid):
Stable under normal conditions.

INCOMPATIBILITIES (materials to avoid):
Avoid contact with acids, and oxidizing agents.

DECOMPOSITION:
Thermal decomposition products include: carbon monoxide, carbon dioxide, oxides of nitrogen and other nitrogen compounds such as hydrogen cyanide.
Decomposition begins at 310° C.

HAZARDOUS POLYMERIZATION:
Not known to occur

SECTION 11 - TOXICOLOGICAL INFORMATION

Acute Oral LD₅₀ (rat): Greater than 5000 mg/kg

Product Name: **MX Nylon**

Preparation date: 2/8/05

SECTION 12 - ECOLOGICAL INFORMATION

No data available

SECTION 13 - DISPOSAL CONSIDERATIONS

Deposit in a landfill in accordance with applicable local, state and Federal regulations. This material, if disposed of, is not considered a hazardous waste under current RCRA definitions.

SECTION 14 - TRANSPORT INFORMATION

Not regulated by current DOT, IMO or ICAO regulations.

SECTION 15 - REGULATORY INFORMATION

TSCA INFORMATION:

All components in this product are in compliance with TSCA Inventory requirements.

CEPA INFORMATION:

This material has been added to the Canadian DSL (Canada Gazette Dec. 19, 2001)

SARA 313 INFORMATION:

SARA requires submission of annual reports of release of toxic chemicals that appear in 40 CFR 372. This information must be included in all MSDS that are copied and distributed for this material.

Components present in this product at a level that could require reporting under the statute are: None

CALIFORNIA PROPOSITION 65:

This product is not, to the best of our knowledge, subject to the labeling requirements under California Proposition 65.

FDA STATUS:

This product is approved for use under 21 CFR 177.1390 and 177.1500, subject to certain limitations.

Product Name: **MX Nylon**

Preparation date: 2/8/05

SECTION 16 - OTHER INFORMATION

HAZARD RATING:

HEALTH	0	0 - LEAST
FIRE	1	1 - SLIGHT
REACTIVITY	0	2 - MODERATE
OTHER	-	3 - HIGH
		4 - EXTREME

HAZARD RATING METHOD: HMIS

REASON FOR REVISION:

Changed company address and phone number

The product information contained herein is believed to be accurate as of the date of the Material Safety Data Sheet, and is provided without warranty, expressed or implied, as to the results of use of this information or the product to which it relates. Recipient assumes all responsibility for the use of this information and the use (alone or in combination with any other product), storage or disposal of the product, including any resultant personal injury or property damage.

****END OF REPORT****